

SATO-Direct 225CT

FACESHEET

Basis Weight (lb/ream)	50
Caliper Target (mils)	3.2
Tensile MD Target (lb/in)	35
Tensile CD Target (lb/in)	14
Tear MD (grams)	50
Tear CD (grams)	55
Stiffness MD (grams)	
Stiffness CD (grams)	
Color	White

ADHESIVE

Description	Rubber Cold Temperature
Caliper Target (mils)	0.7

LINER

Description	Glassine
Caliper Target (mils)	1.6

TOTAL CALIPER

Caliper Target (mils)	5.5
-----------------------	-----

ENVIRONMENT

Storage Temperature (°F)	40	to	72
Storage Humidity (%RH)	35	to	75
Shelf Life (months)	12		
Min Application Temp (°F)	-10		
Service Temperature (°F)	-65	to	120

SPECIAL NOTES:

Offers a thin liner allowing additional labels per roll.

FACESHEET TYPE

- ✓ Paper
- Film

PRODUCT TYPE

- ✓ Label
- Tag
- Receipt

IMAGING CAPABILITY

- ✓ Direct Thermal
- Thermal Transfer - Wax
- Thermal Transfer - Wax/Resin
- Thermal Transfer - Resin
- Laser

AGENCY RECOGNITION

- UL
- cUL
- FSC
- FDA.21 CFR 175.105
- ✓ BPA Free

MAXIMUM OUTDOOR LIFE

- ✓ For Indoor Use only
- <6 months
- <12 months
- <18 months
- 2 years

The above data represents product averages, allowing for industry accepted variances. These products should be tested in the end-use conditions to ensure that they meet the requirements of the specific application. Specification may change without notice.

SATO AMERICA

CORPORATE
14125 South Bridge Circle
Charlotte, NC 28273
Phone: (704) 644-1650
sales-sal@sato-global.com

LABEL MANUFACTURING, SERVICE & SALES
UNITED STATES MEXICO CENTRAL AMERICA
CANADA CARIBBEAN

www.satoamerica.com

