SF300 DuraMark Gloss Polyester

C302471287LS

FACESHEET	
Basis Weight (lb/ream)	
Caliper Target (mils)	2
Tensile MD Target (lb/in)	21.3
Tensile CD Target (lb/in)	28.4
Tear MD (grams)	
Tear CD (grams)	
Stiffness MD (grams)	
Stiffness CD (grams)	
Color	White

ADHESIVE	
Description	Emulsion Acrylic Permanent
Caliper Target (mils)	0.8

LINER	
Description	50# SCK
Caliper Target (mils)	3.2

TOTAL CALIPER	
Caliper Target (mils)	6

ENVIRONMENT			
Storage Temperature (°F)	40	to	72
Storage Humidity (%RH)	35	to	75
Shelf Life (months)	12		
Min Application Temp (°F)	25		
Service Temperature (°F)	-40	to	300

FACESHEET TYPE	
	Paper
✓	Film

PRODUCT TYPE	
✓	Label
	Tag
	Receipt

IMAGING CAPABILITY	
	Direct Thermal
	Thermal Transfer - Wax
	Thermal Transfer - Wax/Resin
✓	Thermal Transfer - Resin
	Laser

AGENCY RECOGNITION	
✓	UL
	cUL
	FSC
✓	FDA.21 CFR 175.105
	BPA Free

MAXIMUM OUTDOOR LIFE	
	For Indoor Use only
	<6 months
	<12 months
	<18 months
✓	2 years

SPECIAL NOTES:

The above data represents product averages, allowing for industry accepted variances. These products should be tested in the end-use conditions to ensure that they meet the requirements of the specific application. Specification may change without notice.

SATO AMERICA

CORPORATE
14125 South Bridge Circle
Charlotte, NC 28273
Phone: (704) 644-1650
sales-sal@sato-global.com

LABEL MANUFACTURING, SERVICE & SALES
UNITED STATES MEXICO CENTRAL AMERICA
CANADA CARIBBEAN

www.satoamerica.com

©2021 SATO America . All rights Reserved.• Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.

8/4/2021